

MRCC 1000

Mold Resistant Clear Coat

MRCC 1000 is a mold resistant clear coating for professional use, that contains an EPA registered fungicide to resist mold growth on the dry coating surface. MRCC is a durable, flexible, and permeable 100% acrylic water-based coating. MRCC is recommended for use on wood, plaster, wallboard, sheetrock, concrete, masonry block, primed metal and galvanized metal. MRCC can also be used on new structural materials during building construction.

SURFACE PREPARATION: Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with OXY BLAST, or use an EPA registered antimicrobial disinfectant cleaner such as Milban 1-2-3 or Sani Spray. Patch irregularities with vinyl patching paste or an appropriate patching compound. MRCC is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

DIRECTIONS : Apply MRCC with brush, roller or airless spray equipment.

Brush: Synthetic, nylon or polyester bristle Roller: Synthetic Fiber 3/8" nap or longer Spray: .015 to .019 tip @ 2000-2800 P.S.I.

PRODUCT APPLICATION: MRCC is supplied ready to use, but can be thinned sparingly with water (up to 8oz of water per gallon) for proper application consistency if necessary. Apply MRCC generously and uniformly by brush, roller, or airless spray. Apply one coat of MRCC and ensure that the finished surface is properly sealed. To ensure that the finished surface is properly sealed, two-coats may be required on some porous surfaces.

COVERAGES: smooth Surfaces: 350-600 ft²/gal. Porous Surfaces: 250-300 ft²/gal.

DRYING TIME: @ 70°F 50% R.H To Touch: 1 Hour Recoat: 4-8 Hours

CLEANUP: Clean tools and drippings with warm soapy water before MRCC dries. Dispose of waste according to all existing local, state and federal regulations.

